



Security

User manual for removing the light source and separate control gear in the Lily LED mirror bathroom cabinet

1. Connect the power plug to the socket. Activate the light source with the button in the middle of the cabinet.
2. Perform a visual inspection on the front and back of the product to determine the position of the light source and separate control gear within the product.
3. Disconnect the product from the light source.
4. Place the cabinet vertically, then, using a drill-driver or screwdriver, unscrew the two hangers on the back of the cabinet and put them in a safe place with the screws.
5. Unscrew the back plate of the cabinet using a drill-driver or a screwdriver.
6. Disconnect the separate control gear with the wago couplings located in the center.
7. Using a knife, cut off the control gear from the cabinet.

Preparation of the cabinet for the panel removal

8. Unscrew the door from the cabinet.
9. Remove the cover in the surface profile with a flat screwdriver or a knife.
10. Cut the acrylic or glue at the joint of the surface profile and the front surface of the cabinet.
11. Using a knife, cut the light source from the wires, then peel off the LED strip from the strip.

Removing the profile with LED lighting

12. Using a knife or flat screwdriver, open the profile to remove the plug, then peel the profile off to separate it from the cabinet.
13. Using a knife, cut off the light source from the wires, then remove the LED strip from the profile.

Location of the internal recessed profile with LED lighting

14. The internal recessed profile with LED lighting is located inside of the cabinet.
15. Using a knife or flat screwdriver, open the profile to remove the plug, then peel the profile off to separate it from the cabinet.